Xerox® Color C60/C70 Printer
Color Multifunction Printer

To interactively build and configure your own Xerox® Color C60/C70, please visit **www.buildyourownxerox.com**.

	Xerox® Color C60 Printer		Xerox® Color C70 Printer	
Simplex Speeds	**Color**	**Black-and-white**	**Color**	**Black-and-white**
8.5 x 11 in. / A4 64 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	 Up to 60 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	 Up to 65 ppm Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	 Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	 Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
11 x 17 in. / A3 64 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	 Up to 30 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	 Up to 33 ppm Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	 Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	 Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
12 x 18 in. / SRA3 64 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	 Up to 27 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	 Up to 29 ppm Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	 Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	 Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm
Auto Duplex Speeds	**Color**	**Black-and-white**	**Color**	**Black-and-white**
8.5 x 11 in. / A4 Example: 64 to 105 gsm uncoated	Up to 60 ipm 2-sided 30 sheets per minute	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 35 sheets per minute
11 x 17 in. / A3 Example: 64 to 105 gsm uncoated	Up to 30 ppm 2-sided 15 sheets per minute	Up to 33 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute
Device Specifications				
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis).[1]			
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month[2]			
Technology	Xerox® EA toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			

Xerox® Color C60/C70 Printer

Accessories			
Optional	Offset Catch Tray High Capacity Feeder (A4) 1 Tray Oversized High Capacity Feeder with Storage Bin 2 Tray Oversized High Capacity Feeder Interface Module BR Finisher (includes Vertical Transport Kit) BR Booklet Maker Finisher (includes Vertical Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher Standard Finisher (requires Interface Module) Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ (requires Interface Module and Standard Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Standard Finisher with Booklet Maker) Convenience Stapler Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow Print Server Integrated for the Xerox® Color C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery® Foreign Device Interface Kit Mobility Plate Envelope Fuser Kit USB Hub XMPie® Variable Data Printing PostScript Kit (recommended for Xerox® Integrated Color Server for the Xerox® Color C60/C70 – PostScript Kit not used with Fiery or FreeFlow Print Servers) Media Card Reader VOIP Fax 1 (3 Line Outside N. America) Fax Kits Server Fax Kit Common Access Card Enablement Kit Xerox® Scan to PC Desktop® Xerox Secure Access Unified ID System® Equitrac Office®		
Electrical Requirements			
North America	Voltage: 110-127V Frequency: 50/60 Hz +/- 3%, 20 A		
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A		
Accessories North America: Europe:	 Each module requires 120V, 15 A Each module requires 220V, 10 A		
Power Consumption			
Running (Average)	1,052 watts (Preliminary value. Pending final report)		
Low Power Mode (Average)	< 131 watts (Preliminary value. Pending final report)		
Sleep Mode (Average)	1.3 watts (Preliminary value. Pending final report)		
Low Power Mode Recovery Time	30 seconds		
Operating Environment			
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)		
Required Relative Humidity	15% to 85% (no condensation)		
Sound Power Levels	Operating 48.8 dB(A), Standby: 40.9dB(A) (Preliminary value. Pending final report)		
Weight (approximate base unit only)	604 lb., 273 kg		
Dimensions	**Width**	**Depth**	**Height**
Base Unit with Offset Catch Tray	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Finisher	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Booklet Maker Finisher	81.4 in. / 2,068 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Standard Finisher	97.7 in. / 2481 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Booklet Maker Finisher	122.9 in. / 3,121.7 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
GBC® AdvancedPunch™	12 in. / 305 mm	28.5 in. / 724 mm	38.5 in. / 978 mm
Xerox® SquareFold® Trimmer	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm

High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm
One Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Two Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Certifications			
	WHQL certification (depending on print server / controller selected) Citrix MEDITECH SAP Common Criteria (pending) ENERGY STAR® Environmental Choice EPEAT GS Mark NOM EAC/GOST To view the latest list of certifications, go to **www.xerox.com/OfficeCertifications**.		
Graphic Arts Credentials			
	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) *requires an additional Print Server option		
Paper Handling			
Single-pass Automatic Document Feeder			
Capacity[3]	250 sheets of plain paper – 20 lb. / 75 gsm		
Speed	Up to 200 ipm color / 200 ipm black-and-white (2-sided, 8.5 x 11 in. / A4)		
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 to 53 lb. bond / 38 to 200 gsm		
Bypass Tray			
Capacity[3]	Up to 250 sheets		
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in. / 102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)		
Envelope Capacity	30 to 50 envelopes		
Envelope Sizes	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5. Paper Size Default within tools) run flap open at the trail edge) Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in. / 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended		
Envelope Weights	75 to 90 gsm		
Trays 1 to 4			
Capacity[3]	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets		
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4		
Weights	18 lb. bond to 80 lb. cover / 64 to 220 gsm (uncoated and coated)		
Optional High Capacity Feeder (HCF)			
Capacity[3]	2,000 sheets		
Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)		
Weights	18 lb. bond to 80 lb. cover / 64 to 220 gsm (uncoated and coated)		
Optional Oversized High Capacity Feeder (OHCF) – 1 or 2 Tray Options			
Capacity[3]	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets		
Sizes	1 Tray OHCF: 7.2 x 10 in. / 182 x 250 mm (B5) to 13 x 19.2 in. / 330 x 488 mm (SRA3) 2 Tray OHCF: 4 x 6 in. / 102 x 152 mm to 13 x 19.2 in. / 330 x 488 mm (SRA3)		

Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)
Total Capacity	
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder)
Automatic Two-Sided	• 65 lb. cover / 176 gsm auto duplex for all stocks • 80 lb. / 220 gsm auto duplex includes A4 / Letter / A3 / Tabloid (excludes 12 x 18 in. / SRA3) • 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder
Finishing	
Offset Catch Tray	
Capacity[3]	500-sheet stacking
Optional BR Finisher (Requires Vertical Transport Kit)	
Capacity[3]	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Optional BR Booklet Maker Finisher (Requires Vertical Transport Kit)	
Capacity[3]	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported
Optional C Fold / Z Fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)	
Types	C Fold, Z Fold and Z Half Fold
Capacity[3]	40 sheets
Sizes	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only
Weights	16 lb. to 24 lb. bond / 64 to 90 gsm
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
Optional Standard Finisher (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm

Hole-punching North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	 200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Optional Standard Finisher with Booklet Maker (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	 2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	 200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated) Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3
Optional GBC® AdvancedPunch (Optional with Standard Finisher – requires Interface Module)	
Punch Configuration Sizes	8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm
Weights	20 lb. bond to 80 lb. cover / 75 to 216 gsm (uncoated and coated)
	Wide selection of slide-in / slide-out GBC punch die sets available
Optional Xerox® SquareFold® Trimmer Module (Optional with Standard Finisher – requires Interface Module)	
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm
Sizes	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Convenience Stapler	
Capacity	50 sheets (24 lb. / 90 gsm media)
Print	
Print Resolution	Up to 2400 x 2400 dpi
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
Registration	• Advanced registration technology for tighter control • Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available with Xerox® EX C60/C70 Print Server Powered by Fiery® and Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer) • + 1.2 mm front to back registration
First-print-out Time	PS- A4 LEF Simplex Color 10.4 seconds / Black-and-white 8.5 seconds
Print Features	• A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing • Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish • Makes mobile printing simpler and more convenient • Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm • Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device • Your choice of servers to best fit your environment: – Xerox® Integrated Color Server for the Xerox® Color C60/C70 Printer – Xerox® EX-i C60/C70 Print Server Powered by Fiery® – Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer – Xerox® EX C60/C70 Print Server Powered by Fiery® • Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters • Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support

Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Copy	
First-copy-out Time From the Platen: From the DADF:	 As fast as 7.8 seconds color / 5.1 seconds black-and-white As fast as 9.6 seconds color / 5.3 seconds black-and-white
Warm Up Time	90 seconds (from cold powered down to Ready Copy)
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation
Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages
Special Features	Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto color selection Area Designation Poster mode Annotation Single/Dual color Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet Insert Stamping 2-in-1 X Y Zoom Zoom Range 25 to 400% Margin Shift Photo Mode Poster Mode Preset Reduce / Enlarge Program Ahead Covers Erase, Image Repeat, Image Rotate Interrupt Job Build Job Program

Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job
Input Speed	Up to 200 images per minute color and black-and-white
Resolution	600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi
Maximum Scan Area	Originals up to 11 x 17 in. / A3
Network Print Services	Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release
File Formats	PDF Image Only PDF (Searchable) PDF (Linearized) PDF (A-1 Level A) TIFF V6 JFIF XPS
Document Management Fields (Metadata)	One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard
Scan Features	Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP Scan via NDS Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to Remote Printer Scan to Fax Server Scan to Multiple Destinations Scan to Documentum Scan to DocuShare Scan to Domino Scan to Hummingbird Scan to Interwoven WorkSite Scan to Live Link Enterprise Server Scan to Microsoft Dynamics GP Scan to MS Exchange web folder Scan to Microsoft SharePoint Scan to SharePoint Portal Server Scan to Thompson ProLaw Scan to Tower TRIM Scan to Web URL Scan to Microsoft Network Folder Scan to Exact e-Synergy
Supported Scan Destinations (Standard)	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public)

Scan to Email Features	Color scanning, Auto Color, Grayscale, Black-and-white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job
Supported Scan Destinations (Optional)	Options include Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
Authentication	SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)
Xerox® ConnectKey® for SharePoint® (Optional)	Xerox® ConnectKey for SharePoint simplifies and streamlines the way you scan, capture and store your paper-based documents. Using your Xerox® MFP, you can route documents directly into the precise document repository folder, just like you would from your PC. At the MFP, you can browse to the folder, name the document, and add any key indexing information before you scan. With the flexibility to capture and route to SharePoint as well as Windows folders, ConnectKey is the right solution for any office that needs to archive and share paper-based documents.
Fax (Optional) – One or Three Line Fax Options	
Compatibility	Color, Auto Color, Black-and-white
Maximum Scan Area	11 x 17 SEF
Fax Send Features	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Fax Print Features	Print from USB Storage Device Media Print Unicode Printing
Fax Features	iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination
Device Management	
Xerox® CentreWare® Internet Services – Integrated Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts
Job Submission	Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination)Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox® MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.

Xerox® Color C60/C70 Printer

Security	
Features	Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication Xerox Secure Access Unified ID System® IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria (pending)
Xerox Secure Access Unified ID System® (Optional)	Xerox Secure Access Unified ID System integrates your Xerox® multifunction systems with your existing employee / student ID PIN or badge providing a flexible and convenient authentication system. Allow your staff, employees or students to send documents to a centralized print server. Then, at any multifunction printer on the network, they'll simply log in with a swipe of their magnetic or proximity ID card or their PIN to securely print their job. For more information, go to **www.office.xerox.com/software-solutions**.
Print Server	
Xerox® Integrated Color Server for the Xerox® Color C60/C70 Printer	
Processor	993 MHz
Memory (ESS)	2 GB RAM
System Disk	80 GB Hard Disk Drive
Display	10.4 in. color touchscreen flat-panel
Device Operating System	VxWorks
Page Description Languages	PDF XPS®, PCL® 6 emulation HP-GL2 (direct submission) Adobe® PostScript® 3™ option TIFF JPEG
Operating Systems	Windows® XP SP1 & above (32 & 64 bit) Server 2003 / 2008 (32 & 64 bit) Vista (32 & 64 bit) Windows 7 (32 & 64 bit) Mac OS® 10.4 and above Citrix® Custom driver for UNIX: – AIX® 5 v5.3 – HP-UX® 11.0 / 11i v2 – Solaris® 8/9/10 – Linux® Fedora Core® 1/5 – Red Hat® ES4 – SUSE® 10/11
Print Drivers Supported	Windows 2003/XP 32 Bit Windows 2003/XP 64 Bit Windows Vista/Vista 32 Bit Windows Vista/Vista 64 Bit Windows 7 / 2008 32 Bit Windows 7 / 2008 64 Bit (Microsoft certified) Macintosh® OS 10.3.0 and UNIX N/A Bi-directional with Xerox Custom Xerox® Mobile Express Driver® XPS Print Driver Xerox® Global Print Driver®

Xerox® Color C60/C70 Printer

Features	• Automatic two-sided • Bi-directional Print Drivers provide device and job status • Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) • Secure print • Delay print • Embedded Web server for remote control/monitor/setup • Enhanced Gloss • Sample set • Booklet creation • Cover selection • Paper selection by attribute • N-up • Watermarks • Banner sheets • Fit to new paper size • Output tray selection • Print calibration • Print from USB Plus more!
Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
	For more information, go to **www.xerox.com/C70IntegratedColorServer**.
Additional Print Server Options	
Xerox® EX-i C60/C70 Print Server Powered by Fiery®	
Processor	Intel® Pentium® G850 Processor, E200, 2.90 GHZ
Memory (ESS)	2 GB
System Disk	500 GB
Print Languages (PDL)	Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9
Features	• Productivity starts with a fast RIP. The Integrated Fiery Color Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and color-critical PDFs accurately and quickly. • Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. • Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. • Get the color right. Produce precise, exact color from all applications, platforms and formats with Fiery color management tools. • Turn up the impact with variable information. Customize your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Color Server's basic variable data printing capabilities.
Connectivity	Direct Connection (Single IP)
	For more information, go to **www.xerox.com/C70EXiFieryColorServer**.
Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer	
Processor	Intel® Dual Core Pentium G3420 Processor
Memory (ESS)	8 GB
System Disk	1 TB 7200 SATA or equal
Print Languages (PDL)	True Adobe® PostScript® Level 1, 2, 3; Adobe® Acrobat® 9.0, PDF 1.8, PDF/X; TIFF, PCL 5c, PCL 6XL, EPS, JPEG
Features	Simple • Windows 7 platform for a familiar experience • Integrated / Bustled setup. Perfect for small footprint and quick and easy site setups • Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) Productive • All the advantages of a Xerox Production workflow – delivered in a value-oriented solution • Streamlined drag/drop submission from tablets and more Powerful • Bring the power of Xerox® patented RIP technology in a value oriented solution • Latest direct Adobe PDF Print Engine and GC credentials included • Includes Variable Data Print / Color Management / Production Workflows Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support
Connectivity	Direct Connection (Single IP)
	For more information, go to **www.xerox.com/C70FreeflowPrintServer**.
Xerox® EX C60/C70 Print Server Powered by Fiery®	
Processor	Intel® Core i5-2400, 4 Core, PRO80-IV, 3.10 GHz
Memory (ESS)	4 GB
System Disk	1 TB

Xerox® Color C60/C70 Printer

Print Languages (PDL)	Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP
Features	• Fiery technology increases your profits by delivering high-impact documents with vibrant images and color that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colors. This feature also eliminates the need to re-program jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalized communications and packaging and photo publishing applications. • Fiery ColorWise gives high-quality color out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Color Profiler Suite to control and manage color throughout your workflow. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralizing job management via its intuitive user interface. Simplify your labor-intensive document composition and imposition tasks even more by using Fiery SeeQuence Impose and Compose's intuitive interface. • Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. • Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless connectivity to Xerox® FreeFlow® for workflow automation.
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)
	For more information, go to **www.xerox.com/C70EXPrintServer**.

Supplies	Description	Yield	Part Number
Customer Replaceable Items			
Toner Cartridges (Metered)	Black	30,000 pages[4]	006R01521
	Cyan	34,000 pages[4]	006R01524
	Magenta	32,000 pages[4]	006R01523
	Yellow	34,000 pages[4]	006R01522
Toner Cartridges (Sold)	Black	30,000 pages[4]	006R01655
	Cyan	34,000 pages[4]	006R01656
	Magenta	32,000 pages[4]	006R01657
	Yellow	34,000 pages[4]	006R01658
Black Drum Cartridge	1 Cartridge	190,000 pages[4]	013R00663
Color Drum Cartridge	1 Cartridge per Color	85,000 pages[4]	013R00664
Charge Corotron	For Black Drum	190,000 pages[4]	013R00650
Fuser	110V 220V	200,000 pages[4] 200,000 pages[4]	008R13102 008R13065
Waste Toner Container	1 Cartridge	50,000 pages[4]	008R12990
Feed Roll Kits	1 Assembly	300,000 pages[4]	008R13169
Staple Cartridges	For BR Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	For BR Booklet Maker Finisher (4 cartridges per carton)	5,000 each cartridge	008R13177
	Staple Cartridge and Waste Container for Standard Finisher	5,000 each cartridge	008R13041
Staple Refills	For BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941

[1] Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.
[2] Expected regular monthly throughput.
[3] Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
[4] Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

To view a product video, visit **www.xerox.com**. Build and configure your own Xerox® Color C60/C70 Printer at **www.buildyourownxerox.com**.

©2014 Xerox Corporation. All Rights Reserved. Xerox®, Xerox and Design®, CentreWare®, ConnectKey®, FreeFlow®, MeterAssistant®, Scan to PC Desktop®, SMart Kit®, SMARTsend®, SquareFold®, SuppliesAssistant®, Xerox Extensible Interface Platform® and Xerox Secure Access Uniifed ID System® and are trademarks of Xerox Corporation in the United States and/or other countries. EFI, Splash, Fiery® and RPX-iii are trademarks of Electronics for Imaging, Inc.
Product appearance, build status and/or specifications are subject to change without notice. Updated 9/14 BR10744 X60SS-01UA